

Professional FM Interpretation System

The PRO-T800 is a complete language interpretation system designed for optimum portability and functionality. The system can have two interpreters working per language and is equipped separate volume and tone control, two microphones, and two headphones for the interpreters with microphone soft-button selectors for seamless and quiet segues between interpreters and language.

The PRO-T800 offers 17 wide-band channels to choose from. Top audio quality is assured by its superior low noise circuitry and sophisticated audio processors. System covers up to 1,000,000 square feet and capable of broadcasting to over 75,000 people. Combining more than one PRO-T800 system provides the ability to handle multiple languages and utilize the 'RELAY' interpreting function of the system. Additional IC2 connect via CAT5 Cable.



Price \$4,499.00

PRO-T800 SYSTEM COMPONENTS

Monitoring

- 1-IC-2 Interpreter Console
- 2-PC151 Headphones Microphone

Transmission

- 1-T45 Large Area Transmitter

Receivers

- 10-R38 Multi Channel Receivers
- 10-HED021 Executive Headsets

Accessories

- 1- Mil-Grade Wheeled Carrying Case
- 2- XLR/XLR Connecting Cables

Interpreter Booths (may be added at additional cost)

- LB12 Tabletop Interpretation Booth
- (70" X 35" X 35" - 70 lbs.)

Multiple Languages

- (1) T45 Transmitter, (1) IC2 Console and (2) PC151's
- CAT5 cable and XLR Cables

Quick Specs

Receiver Channels:	17 (built-in channel selector)
Transmitter Channels:	60 (selectable to any one)
Packed Dimensions:	24" X 14" X 8"
Weight:	33 lbs.
Operating Freq:	72-76 MHz
Range:	0-1,000 feet radius (320m) **

Technical Overview

R38 Receiver	Black
Dimensions:	3.5" X 4" X 0.6" - Wt. 3.5 oz.
Operating Freq:	72-76 MHz (0.025 Hz)
Earphone:	1/8" Mono Jack
Controls:	Volume, Channel Selector
Power Source:	2xAA 1.5V Battery
Battery Life:	60-80 hours (Alkaline)
T45 Transmitter	Black
Dimensions:	8.45" x 8.25" x 1.72" 3.0 lbs (1.36kg)
Transmitter Channels:	60 (selectable to any one)
Range:	0-1,000 feet radius (320m)**
Audio Output:	Line Level RCA & 1/4" Headphone
Audio Input:	Mic/Line Level (XLR or 1/4")
Power Source:	120VAC Adapter (220V available)
IC2 Interpreter Console	Black
Dimensions:	10"x6.35"x2.45" 3.4 lbs 3. (1.5kg)
Controls:	Dual Tone (Hi & Bass) Volume Controls (2), Mute/Cough, Relay, Monitoring Selector, Mic on/off
Audio Input/Output:	Mic (XLR, 1/8"), Line Level (XLR)
Connections:	XLR Line In, RCA Recording, CAT5e Headphone Jacks (x2) 1/8"
Power Source:	120VAC Adapter (220V available)

PRO-T800 - 4 Steps to Quality Interpretation (PMTR)



P- Presentation, **M**- Monitoring, **T**- Transmission, **R**- Reception