

Portable FM Interpretation System

The VP-T100 is complete transportable solution with the ability for an interpreter to monitor the presenter/s directly in her headphone (this greatly enhances concentration and quality of interpretation) and in turn enables the interpreter to broadcast the target language wirelessly in almost any size room.

The VP-T100 can be customized for to accommodate up to eight (8) languages. The VP-T100 can be upgraded to broadcast to over 1,000 listeners. This system is easy-to-use and dollar-for-dollar the most complete system available anywhere at this price level.

More sophisticated systems are available; please call a representative for assistance.



Price \$2,691.40

VP-T100 SYSTEM COMPONENTS

- Monitoring
 - 1- Monitoring Unit
 - 1- Headphone Microphone
- Transmission
 - 1- RF Medium Area Transmitter
- Receivers
 - 10- Seekable Channel Receivers
 - 10- HED021 Executive Earphone
- Accessories
 - 1- 2015 Wheeled Carrying Case w/Retracting Handle
 - 1- XLR<>XLR Connecting Cable
 - Batteries are included

Multiple Language – Upgrade pieces per added language

- 1- Monitoring Unit
- 1- Headphone Microphone
- 1- RF Medium Area Transmitter

#- Eight Channel Selector Receivers

Size and Dimensions	
Receiver Channels:	Seekable function - 8 channels
Transmitter Channels:	10 (selectable to any one)
Packed Dimensions:	20" X 14" X 11"
Weight:	30 lbs.
Operating Freq:	72-76MHz
Range:	0-500 feet (Radius)
Audio Output:	None

Technical Data	
Receiver Color:	Black
Dimensions:	3.5" X 4.25" X 0.6" - Wt. 3.5 oz.
Operating Freq:	72-76MHz
Earphone:	1/8" Mono Jack
Controls:	Volume, Channel Seek Button
Power Source:	2x1.5V Battery
Battery Life::	18-80 hours (Alkaline)

Transmitter Color:	Black
Dimensions:	1.7" X 6" X 4" - Wt. 1.8 lbs.
Operating Freq:	72-76MHz
Power Source:	120VAC Adapter
Output Connector:	N/A

Monitoring Unit:	Black
Dimensions:	3.5" X 3.5" X 2.5" Wt. 0.5 lbs.
Controls:	Mic Volume, Line Volume
Audio Input/Output:	Mic (XLR), Line Level (1/4")
Connections:	XLR Mic In, 1/4" Line In, 1/4" Mic Thru (Out) XLR
	1/8" & 1/4" Headphone Jack
Power Source:	102VAC Adapter

VP-T100 - 4 Steps to Quality Interpretation (PMTR)



P- Presentation, M- Monitoring, T- Transmission, R- Reception